



PRODUCT DATASHEET



PRODUCT TYPE	COFFEE-MAKER
PRODUCT NAME	DOUBLE FANTASIA



PRODUCT DATASHEET

INDEX

- | | |
|---------------------------------|--------|
| 1. TECHNICAL DATA | pag. 3 |
| 2. DESCRIPTION OF THE APPLIANCE | pag. 4 |



PRODUCT DATASHEET

1. TECHNICAL DATA

SIZE	WEIGHT	HEIGHT	LENGTH	DEPTH
2 cups	330 g	12,5 cm	15 cm	12 cm

MATERIAL	<p><u>Aluminum</u> suitable food contact (Boiler, upper part, disk filter, funnel filter)</p> <p>The chemical composition of aluminum and aluminum alloys used by GAT are conform to the standards UNI EN 601/602 (Aluminum and aluminum alloys suitable food contact)</p>
	<p><u>Plastic</u> material (knob)</p> <p>The plastic materials used by G.A.T are conform to the standards DM 21-3-1973 (legislation concerning materials and articles in contact with foodstuffs)</p>
	<p><u>Silicon</u> material (Gasket)</p> <p>The silicon gasket used by G.A.T are conform to the standards DM 21-3-1973 (legislation concerning materials and articles in contact with foodstuffs)</p>



PRODUCT DATASHEET

2. DESCRIPTION OF THE APPLIANCE

The appliance is composed of the following components (Table 1).

Knob	Material: plastic . The knob does not get in touch with coffee.
Boiler and upper part	Material: <u>Aluminum</u> suitable food contact.
Disk filter	Material: <u>Aluminum</u> suitable food contact.
Gasket	Silicon Gasket
Safety valve	<p>Opening pressure of safety valve: 2÷3,5 Bar (in according to UNI EN 13248:2004 - Cookware - Coffee makers for domestic use with an independent heat source -. Definitions, requirements and test methods)</p> <p>Control parameter of safety valve (in according to UNI EN 2859/1):</p> <ul style="list-style-type: none"> - Type of sampling: attributes control - Sampling plan: Simple sampling - Sample units: safety valve - AQL Level: 0
Funnel filter	<p>Material: <u>Aluminum</u> suitable food contact.</p> <p>Dimensional control: conformity of the distance bottom/funnel in accordance with norm UNI EN 13248;2004 (§4.2.6) “Cookware. Coffee makers for domestic use with an independent heat source. Definitions, requirements and test methods”. Acceptance criterion: minimum distance allowed 2 mm</p>

Table n°1 – Components of coffee-maker